

Safety data sheet in accordance with (EC) no. 1907/2006 (amended by regulation (EU) Nr. 453/2010)

Date of issue: 23.04.2015
Date of revision : 29.12.20
Valid from : 29.12.20
Version: 4

Replaces version: 3

Universal THINNER for Pro-Die Spacers,
Pro-Die Hardener and Chameo Die-Spacer
03-2190
THINNER for Pro Seal Wax Sealing 03-2320

Section 1: Identification of the substance/mixture and of the company

1.1 Product Identifier

Substances: Ethylacetate

Index-no.: 607-022-00-5

EINECS: 205-500-4

CAS-no.: 141-78-6

REACH-registration no.: void

Other means or identification: not determined

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: SU 20 health care, thinner for various liquids - dental field –(dental labs).

Uses advised against: Should not be used outside a dental lab.

1.3 Details of the supplier of the safety data sheet

Supplier:

al dente Dentalprodukte GmbH

Street:

Borsigstr. 1

Address / zip-code / town:

D-38644 Goslar

Information contact:

+49 (0) 5321-80031

Phone / Fax / Email:

+49 (0)5321-80031 / +49 (0)5321-50881 / E-Mail: info@aldente.de

1.4 Emergency Telephone Number:

+49 (0) 171 8637790

Section 2: Hazards identification:

2.1 Classification of the substance or mixture:

Classification according to regulation (EC) no. 1272/2008 (CLP)

Flammable liquids (chapter 2.6), category 2 (Flam. Liq. 2), H225,

Eye irritation (chapter 3.3), category 2 (Eye Irrit. 2), H319,

Specific target Organ Systemic Toxicity (single exposure), (chapter 3.8), category 3, (May cause drowsiness or dizziness) (STOT SE 3) H336

For the full text of the H-statements mentioned in this section, see section 16.

2.2 Label Elements

Labelling according to regulation (EC) no. 1272/2008 (CLP/GHS)

Hazard pictograms: GHS02, GHS07



Safety data sheet in accordance with (EC) no. 1907/2006 (amended by regulation (EU) Nr. 453/2010)

Date of issue: 23.04.2015
Date of revision : 29.12.20
Valid from : 29.12.20
Version: 4

Replaces version: 3

Universal THINNER for Pro-Die Spacers,
Pro-Die Hardener and Chameo Die-Spacer
03-2190
THINNER for Pro Seal Wax Sealing 03-2320

Signal word: Danger (Flam.Liq. 2), Warning (Skin Irrit. 2)

Reduced labelling (≤125 ml) (according to exemptions from the packaging and labelling regulations according to EC-CLP-

regulation) Signal word: danger hazard pictograms:



Hazardous component(s) for labelling:

Contains Ethylacetate

Hazard statements:

H225: Highly flammable liquid

H319: May cause serious eye irritation

H336: May cause drowsiness or dizziness

Precautionary statements:

P102: **Keep out of reach of children.**

P210: **Keep away from heat/sparks/open flames/hot surfaces. — No smoking.**

P233: **Keep container tightly closed.**

P305 P351+P338: If in eyes, Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Supplemental Hazard information (EU):

EUH066: Repeated exposure may cause skin dryness or cracking.

Full text of H- and EUH-phrases: see SECTION 16

2.3 Other Hazards:

No supplementary information available.

SECTION 3: Composition/information on ingredients

3.1 Substances

Principal component of the substance:

Substance name: Ethylacetate

Index-no.: 607-022-00-5

EG-no.: 205-500-4

CAS-no.: 141-78-6

Hazard pictograms: GHS02, GHS07



Signal word: Danger (Flam.Liq. 2), Warning (Skin Irrit. 2)

Classification according to regulation (EC) no. 1272/2008 (CLP)

Flammable liquids (chapter 2.6), category 2 (Flam. Liq. 2), H225,

Eye irritation (chapter 3.3), category 2 (Eye Irrit. 2), H319,

Specific target Organ Systemic Toxicity (single exposure), (chapter 3.8), category 3, (May cause drowsiness or dizziness) (STOT SE 3) H336

For the full text of the H-statements mentioned in this section, see section 16.

Safety data sheet in accordance with (EC) no. 1907/2006 (amended by regulation (EU) Nr. 453/2010)

Date of issue: 23.04.2015
Date of revision : 29.12.20
Valid from : 29.12.20
Version: 4

Universal THINNER for Pro-Die Spacers,
Pro-Die Hardener and Chameo Die-Spacer
03-2190
THINNER for Pro Seal Wax Sealing 03-2320

Replaces version: 3

Chemical Identifier (concentration) Ethylacetate (<= 100 %)
This substance does not meet the PBT or vPvB criteria according to the regulation (EC) no. 1907/2006, annex XIII.
CAS-No.: 141-78-6
EC-No.: 205-500-4
Registration no: 01-2119475103-46-XXXX

Impurities, stabilizers:

Substance name: solution of solvents in ethyl acetate
Index-no.: not applicable
EC-no.: not applicable
CAS-no.: not applicable

3.2 Mixtures – not applicable

Description of the mixture:

EG-no.: CAS-no. : Index-Nno.: REACH-registration no.:
Content ration: %
Classification according to regulation (EC) no. 1272/2008 (CLP)

(Full text of H- and EUH-phrases: see SECTION 16)

Section 4: First aid measures

4.1 Description of first aid measures:

In general: take off contaminated clothing

Following inhalation:

In case of dizziness after inhalation of vapors, take the person concerned to fresh air.

Following skin contact:

Wash affected skin thoroughly with water and soap.

Following eye contact:

Rinse eyes with current water for at least 10 minutes. If eye irritation persists consult a doctor.

Following ingestion:

Rinse mouth. If discomfort persist consult a doctor.

4.2 Most important symptoms and effects, both acute and delayed

Irritant effects, drowsiness, nausea, vomiting, headache, doziness.

4.3 Indication of any immediate medical attention and special treatment needed

Notes for the doctor: not determined

Special treatment: not determined

Section 5: Firefighting measures

5.1 Extinguishing media

Suitable: dry powder, foam, sand

Unsuitable: water

5.2 Special hazards arising from the substance or mixture

Flammable. An incomplete combustion may result in toxic components within the flue gas. In case of fire a respiratory equipment working independently from its ambient environment is recommended for the fire fighters.

5.3 Advice for fire-fighters

Safety data sheet in accordance with (EC) no. 1907/2006 (amended by regulation (EU) Nr. 453/2010)

Date of issue: 23.04.2015
Date of revision : 29.12.20
Valid from : 29.12.20
Version: 4

Replaces version: 3

Universal THINNER for Pro-Die Spacers,
Pro-Die Hardener and Chameo Die-Spacer
03-2190
THINNER for Pro Seal Wax Sealing 03-2320

In case of fire a respiratory equipment working independently from its ambient environment is recommended for the fire fighters.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures **For non-emergency personnel**

Remove all sources of ignition immediately. Ensure good ventilation. Do not inhale fume or spray.

For emergency responders

Personal protective equipment:

respiratory equipment working independently from its ambient environment

6.2 Environmental precautions

Prevent the liquids from ingressing into surface water or drains.

6.3 Methods and material for containment and cleaning up

Wear safety equipment, absorb with liquid binding material (sand, universal binding material) and dispose of as hazardous material.

6.4 Reference to other sections

Dangerous combustion products: see section 5. Personal protective equipment: see section 8.

Section 7: Handling and storage

7.1 Precautions for safe handling

No particular measures are necessary when used properly.

Fire preventions:

Provide adequate ventilation. Keep away from sources of ignition – don't smoke!



Aerosol and dust generation preventions:

Not determined

Environmental precautions:

Prevent the liquids from ingressing into surface water or drains.

Advice on general occupational hygiene:

Follow the advice on general occupational hygiene, when dealing with chemicals, keep away from food, don't smoke.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Store under 30°C, tightly closed. Keep away from food.

Requirements for storage rooms and vessels

According to TRGS 510, annex 9, regulation for small quantities

Storage class: (LGK) (VCI) 3

7.3 Specific end uses

Sector specific guidelines: dental laboratories

Except for the applications mentioned in section 1.2 there are no other specific end applications provided.

Safety data sheet in accordance with (EC) no. 1907/2006 (amended by regulation (EU) Nr. 453/2010)

Date of issue: 23.04.2015
Date of revision : 29.12.20
Valid from : 29.12.20
Version: 4

Replaces version: 3

Universal THINNER for Pro-Die Spacers,
Pro-Die Hardener and Chameo Die-Spacer
03-2190
THINNER for Pro Seal Wax Sealing 03-2320

Section 8: Exposure controls / personal protection

8.1 Control parameters

Occupational exposure limits

Substance: Ethylacetate ; CAS-no. 141-78-6
Specification : TRGS 900 exposure limits
Limit value type (country of origin) : 400 ml/m³
Peak limitation: Exceedance factor (ÜF) 2, category for short term values II
Toxic to reproduction: A risk of foetal damage is ceased to fear when observing the MAK / BAT values.
Source (TRGS) Not determined

8.2 Exposure controls

Appropriate engineering controls

Personal protective equipment

Eye / face protection



Wear tight fitting goggles

Skin protection

Hand protection

The glove material has to be impermeable and resistant to the product.

Full contact:

Gloves made of butyl rubber.

Layer thickness: $\geq 0,7$ mm

Penetration time: ≥ 60 min



Splash contact:

Gloves made of nitrile rubber

Layer thickness: 0,40 mm

Penetration time: < 120 min.

Body protection

Wear adequate working clothes.

Respiratory protection

Generally there are no specific measures to be taken. In case of release of a more important quantity (drained off bottle) provide for sufficient ventilation.

Thermal hazards

Not applicable if not stored over 45°C for a longer space of time.

Safety data sheet in accordance with (EC) no. 1907/2006 (amended by regulation (EU) Nr. 453/2010)

Date of issue: 23.04.2015
Date of revision : 29.12.20
Valid from : 29.12.20
Version: 4

Replaces version: 3

Universal THINNER for Pro-Die Spacers,
Pro-Die Hardener and Chameo Die-Spacer
03-2190
THINNER for Pro Seal Wax Sealing 03-2320

Environmental exposure controls

Not determined

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties:

Physical state:
Aggregate state: liquid
colour : transparent
Odour : specific
Odour threshold : not determined
pH-value: not determined
Melting point / freezing point : Not determined
Initial boiling point/boiling range : 75-77°C
Flash point: - 1°C
Evaporation rate : not determined
Flammability: 460°C
Upper/lower explosive limits: 11,5 %(V) - 2,1 %(V)
Vapour pressure : not determined
Vapour density: not determined
Relative density: not determined
Solubility: 79 g/l
Partition coefficient: not determined
n-octanol/water: not determined
Auto-ignition temperature: not determined
Decomposition temperature: not determined
Viscosity: not determined
explosive properties: considered as being non-explosive
Oxidising properties: not determined

Other information

9.2

Physical hazards

Explosives There are no further data available

Section 10: Stability and reactivity

10.1 Reactivity:

not determined

10.2 Chemical stability:

Under standard ambient conditions the material is chemically stable.

10.3 Possibility of hazardous reactions:

Contact with strongly oxidizing agents

10.4 Conditions to avoid:

Storing for a longer space of time over 45°C.

10.5 Incompatible materials: oxidizing agents

Safety data sheet in accordance with (EC) no. 1907/2006 (amended by regulation (EU) Nr. 453/2010)

Date of issue: 23.04.2015
Date of revision : 29.12.20
Valid from : 29.12.20
Version: 4

Replaces version: 3

Universal THINNER for Pro-Die Spacers,
Pro-Die Hardener and Chameo Die-Spacer
03-2190
THINNER for Pro Seal Wax Sealing 03-2320

Section 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Oral LD₅₀ 7060 mg/kg (Rat) (TOXNET)
Inhalative LC₅₀/4 h 95,6 mg/l (Rat) (IUCLID)

Skin irritation

Absorption of acute toxics exclusively through skin contact is considered as being quite unlikely.
Repeated or prolonged exposure may cause skin irritation and dermatitis due to degreasing properties of the product (EUH066)

Eye irritation

Result rabbit: weak eye irritation effect

OECD test guideline 405

May cause serious eye irritation (H319)

Sensitisation to the respiratory tract / skin

After inhalation: slight irritation

Germ cell mutagenicity

No known significant effects or critical hazards.

Carcinogenicity

No known significant effects or critical hazards.

Reproductive toxicity

No known significant effects or critical hazards.

Specific target organ toxicity (single exposure): dizziness and sleepiness possible

Specific target organ toxicity (repeated exposure): The substance is not classified on organ toxicity on repeated exposure (see single exposure).

Aspiration hazard

No information available.

Symptoms related to the physical, chemical and toxicological characteristics:

In case of ingestion: no information available

In case of skin contact: frequent contact: dryness

In case of inhalation: no information available

In case of eye contact: no information available

Section 12: Ecological information

12.1 Toxicity

Aquatic toxicity / fish toxicity:

LC₅₀ 8140 mg/l/96 h (Leuciscus idus (Goldorfe)) (IUCLID)

Daphnia toxicity:

EC50 >9000 - <15000 mg/l/48 h (Daphnia magna) (IUCLID)

Algal toxicity:

IC5 5000 mg/l (Scenedesmus quadricauda) (Lit.)

Bacterial toxicity:

EC5 6500 mg/l (Pseudomonas putida) (IUCLID) 16h

12.2 Persistence and degradability

Biodegradability 94 %

OECD test guideline 301E

Easily biodegradable.

Safety data sheet in accordance with (EC) no. 1907/2006 (amended by regulation (EU) Nr. 453/2010)

Date of issue: 23.04.2015
Date of revision : 29.12.20
Valid from : 29.12.20
Version: 4

Replaces version: 3

Universal THINNER for Pro-Die Spacers,
Pro-Die Hardener and Chameo Die-Spacer
03-2190
THINNER for Pro Seal Wax Sealing 03-2320

12.3 Bioaccumulative potential

Bioaccumulation is not to be expected.

12.4 Mobility in soil

No information available

12.5 Results of PBT- and vPvB assessment

Not applicable

12.6 Other adverse effects

No further relevant information available.

Section 13: Disposal considerations

13.1 Waste treatment methods

Contaminated packaging disposal

Containers are to be treated as the product itself. 150110 (AVV)

Waste codes / waste designations according to EWC / AVV:

160506 (AVV)

The product is to be considered as special waste and has to be disposed of according to the national and regional regulations (varnishes).

Special precautions: not applicable

Other relevant provisions for waste treatment national or EC

Waste directive 2008/98/EC has to be observed.

Section 14: Transport information

14.1 UN-no. 1173

14.2 UN proper shipping name

ADR/RID: Ethylacetate

IMDG-Code / ICAO-TI / IATA-DGR: Ethylacetate

14.3 Transport hazard class(es) / hazard labels: 3

14.4 Packing group: II

14.5 Environmental hazards

Environmentally hazardous substance marking

ADR/RID / IMDG-Code / ICAO-TI / IATA-DGR: yes / **XXXXX no**

Marine Pollutant: yes / **XXX no** slightly hazardous to waters

EMS-Code: F-E,S-D

Safety data sheet in accordance with (EC) no. 1907/2006 (amended by regulation (EU) Nr. 453/2010)

Date of issue: 23.04.2015
Date of revision : 29.12.20
Valid from : 29.12.20
Version: 4

Replaces version: 3

Universal THINNER for Pro-Die Spacers,
Pro-Die Hardener and Chameo Die-Spacer
03-2190
THINNER for Pro Seal Wax Sealing 03-2320

14.6 Special precautions for user

Do not expose to sources of ignition. Beware of inflammable materials.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category (X, Y or Z) : not applicable, package size: 20 ml

Type of ship (1, 2 or 3) : not applicable, package size: 20 ml

Section 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-regulations, e.g.:

Directive / EC no. 2037/2000 (substances that deplete the ozone layer): not applicable

Directive / EC no. 850/2004 (persistent organic pollutants): not applicable

Directive / EC no.. 689/2008 (export and import of dangerous chemicals): not applicable

Directive / EC no. 648/2004 (detergent regulation): not applicable

National regulations, e.g.:

Water hazard class: 1

Technical instructions on Air Quality Control (TA-Luft): not applicable

Other relevant regulations

Not applicable

15.2 Chemical safety assessment

No chemical safety assessment has been performed on this substance.

Section 16: Other information

Indication of changes

Adaption to the classification and labelling according to directive (EC) no. 1272/2008

Section 1: Emergency phone number.

Abbreviations and acronyms

n.a. Not applicable

Key literature references and sources for data

Gestis substance data base - <http://gestis.itrust.de/>

Federal Agency for Industrial Health and Safety - www.baua.de

Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP]:

Relevant R-, H- and EUH-phrases (number and full text):

Safety data sheet in accordance with (EC) no. 1907/2006 (amended by regulation (EU) Nr. 453/2010)

Date of issue: 23.04.2015
Date of revision : 29.12.20
Valid from : 29.12.20
Version: 4

Replaces version: 3

Universal THINNER for Pro-Die Spacers,
Pro-Die Hardener and Chameo Die-Spacer
03-2190
THINNER for Pro Seal Wax Sealing 03-2320

Hazard statements:

H225: Highly flammable liquid and vapour.
H319: Causes serious eye irritation.
H336: May cause drowsiness and dizziness

Precautionary statements:

P210: Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P233: Keep container tightly closed.
P102: Keep out of reach of children.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

Supplemental Hazard information (EU):

EUH066: Repeated exposure may cause skin dryness or cracking.

Training advice

Provide adequate information, instruction and training for operators / technicians using this product.

Further information

This information is based on our present state of knowledge. It should therefore not be construed as guaranteeing specific properties of the products described or their suitability for a particular application. We do not take any responsibility for possible sources of errors or sufficiency of this document. The user of the product accepts the sole responsibility to adhere to all herein mentioned regulations. It is the user's obligation to read this document carefully.